FLATPOMP/20

TGMCL 114

IMPIEGO

Tubo in gomma cord per mandata acqua, fertilizzanti e fluidi non corrosivi. Per la sua leggerezza ed appiattibilità trova impiego ideale negli impianti mobili d'irrigazione a pioggia e come accessorio di pompe sommerse.

- ***Temperatura:*** -30°C +80°C

STRUTTURA

- ***Sottostrato:*** liscio in gomma nera EDPM.
- ***Rinforzi:*** tessuti sintetici ad alta resistenza.
- ***Copertura:*** in gomma nera SBR/EPDM resistente all'abrasione e agli agenti atmosferici.
- ***Superficie:*** liscia ad impressione tela.
- ***Marcatura:*** listino a rilievo "H.T. - FLATPOMP/20 – W.P. 20 BAR (300 PSI)"

APPLICATION

Softwall rubber hose suitable for delivery of water and non corrosive fluids. Suitable for submersible pumps and irrigation systems.

- ***Temperature range:*** -30°C +80°C

CONSTRUCTION

- ***Tube:*** black, smooth EDPM rubber.
- ***Reinforcement:*** high strength synthetic textile plies.
- ***Cover:*** black, abrasion and weathering resistant SBR/EPDM rubber.
- ***Surface:*** smooth fabric finished.
- ***Branding:*** embossed "H.T. - FLATPOMP/20 – W.P. 20 BAR (300 PSI)"

DIAMETRO INTERNO *INSIDE DIAMETER*		DIAMETRO ESTERNO *OUTSIDE DIAMETER*		PESO TEORICO *WEIGHT*		PRESS. ESERCIZIO *WORKING PRESSURE*		PRESS. SCOPPIO *BURST PRESSURE*		LUNGHEZZA *LENGTH*	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
51	2"	61	2.3/8"	1.07	0.72	20	300	60	900	20	65.6
60	2.3/8"	72	2.3/4"	1.38	0.93	20	300	60	900	20	65.6
76	3"	88	3.15/32"	1.72	1.16	20	300	60	900	20	65.6
80	3.5/32"	92	3.17/32"	1.87	1.26	20	300	60	900	20	65.6
90	3.17/32"	102	4"	2.10	1.42	20	300	60	900	20	65.6
102	4"	114	4.3/8"	2.33	1.57	20	300	60	900	20	65.6
120	4.3/4"	132	5.3/16"	2.85	1.92	20	300	60	900	20	65.6
152	6"	168	6.15/32"	4.85	3.26	20	300	60	900	20	65.6

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Rev. 1