

S Crimp 350/350L

PE 58 Pro / PE 58 Eco
Full service workshop



- High power & large opening in a very compact design
- Ergonomic micrometer / Easy set up
- Radial Die Movement
- Electronic control including counters & semi-automatic opening
- Cylinder protection
- Groove for 90° long drop
- Die sets available for Industrial hose
- Energy savings
- Automatic Maintenance Alerts

Standard

Options



Ergonomic micrometer



Smart control panel



Marking dies



EG



DST



Electrical footswitch



DSP



Mechanical backstop



Die sets for brake & Air conditioning hoses

Technical features

Capacity	2" 6SP - 4" Industrial
Crimp range	4 - 130 mm
Crimp force	350 t
Opening with dies	+54 mm
Complete opening	180 mm
Master-die length	115 mm
Motor	5,5 kW (4 kW*)
Dimensions*	730 x 483 x 812 mm 260 kg with oil
Packing details*	1170 x 760 x 1100 mm 320 kg
Dimensions	600 x 400 x 750 mm 240 kg with oil
Packing details	1170 x 760 x 1100 mm 300 kg
Voltages available	400V 3PH - 230V 3PH/1PH

* S Crimp 350L only

Dies selection

N°	Dies selection	Lenght	N°	Dies selection	Lenght
4	04-06	56 mm	51*	51-54	110 mm
6	06-08	56 mm	54	54-57	110 mm
8	08-10	56 mm	57*	57-60	110 mm
10	10-12	56 mm	60	60-66	110 mm
12	12-15	56 mm	66*	66-70	110 mm
15*	15-18	56 mm	70	70-73	110 mm
18*	18-21	56 mm	73*	73-76	125 mm
21*	21-24	56 mm	76	76-80	125 mm
24*	24-27	70 mm	80	80-86	125 mm
27*	27-30	90 mm	86	86-90	125 mm
30	30-33	90 mm	90	90-95	125 mm
33*	33-36	90 mm	95	95-99	125 mm
36	36-39	90 mm	99	99-112	125 mm
39*	39-42	90 mm	112	112-117	125 mm
42	42-45	90 mm	117	117-122	125 mm
45*	45-48	100 mm	122	122-130	125 mm
48	48-51	100 mm			

* Die sets included in the standard package.

WWW.TECHMAFLEX.COM

26 av. de la Vertonne - 44120 Vertou - FRANCE
Tel : + 33 (0)2 400 305 01
Fax : + 33 (0)2 400 300 17
info@techmaflex.com

