AIR/20/Y

TGLSL 019

IMPIEGO

Tubo in elastomero sintetico giallo idoneo per mandata di aria compressa e fluidi inerti.

- ***Temperatura:*** -10°C +70°C

APPLICATION

Black synthetic elastomer yellow hose suitable for delivery of compressed air and non corrosive fluids.

- ***Temperature range:*** -10°C +70°C

STRUTTURA

- ***Sottostrato:*** liscio in elastomero nero.
- ***Rinforzi:*** inserzioni di filati sintetici ad alta resistenza.
- ***Copertura:*** in elastomero giallo resistente all'abrasione e agli agenti atmosferici.
- ***Superficie:*** liscia.
- ***Marcatura:*** listino a rilevo "H.T. – AIR COMPRESSED – W.P. 20 BAR (300 PSI) – ISO R 1307"

CONSTRUCTION

- ***Tube:*** black, smooth synthetic elastomer.
- ***Reinforcement:*** high strength synthetic textile yarn.
- ***Cover:*** abrasion and weathering resistant yellow synthetic elastomer.
- ***Surface:*** smooth.
- ***Branding:*** embossed "H.T. – AIR COMPRESSED – W.P. 20 BAR (300 PSI) – ISO R 1307"

DIAMETRO INTERNO *INSIDE DIAMETER*		DIAMETRO ESTERNO *OUTSIDE DIAMETER*		PESO TEORICO *WEIGHT*		PRESS. ESERCIZIO *WORKING PRESSURE*		PRESS. SCOPPIO *BURST PRESSURE*		RAGGIO CURVATURA *BENDING RADIUS*		LUNGHEZZA *LENGTH*	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mm	inch	mt	ft
13	1/2"	22	7/8"	0.30	0.20	20	300	60	900	102	4.00"	40	131
19	3/4"	28	1.3/32"	0.49	0.33	20	300	60	900	152	6.00"	40	131
25	1"	36	1.32/32"	0.66	0.44	20	300	60	900	204	8.00"	40	131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Rev.0