

Bottle Samplers - for use with LPA2 and CML2

Contamination Monitoring Products

11/2016 - rev. 00

BSLPA & BS500

The 110ml & 500ml bottle samplers are suitable for off line and laboratory applications where fluid sampling at point of use is inaccessible or impractical.

A fluid de-aeration facility comes as standard.

Features & Benefits

- ◆ Vacuum feature for de-aeration of fluids
- ◆ Compatible with all portable MP Filtri Contamination Monitoring Products
- ◆Strong Laboratory aesthetic
- ◆Transparent outer for visual indication
- ◆ Full accessories kit included
- ◆Includes carry case (BSLPA)
- ◆Contact MP Filtri for use with fluids other than those stated





Ordering information

Bottle sampler BSLPA

1

2 3

Example:

BSLPA

М

110

BSLPA Bottle sampling unit, suitable for Mineral & synthetic oils.

Bottle sampler BS500

1

2

3

5

Example:

BS500

V

0

0

UK

1 - Version

BS500

2 - Fluid compatibility

V

Viton seals (mineral & synthetc oils and subsea/water based fluids)

Е

EPDM seals (phosphate ester and agressive fluids)

3 - Pressure rating

0

2.5 bar (<68cSt)

н

4.5 bar (>68cSt)

4 - Cylinder type

0

Acrylic cylinder

S

Borosilicate glass cylinder (phosphate esters only)

5 - Power Supply

UK

UK power adapter

EU

European power adapter

US

United States power adapter

CN/AUS

Australasia power adapter