

INTERPUMP HyTruck 250 bar

TTRK250

APPLICATIONS :



APPLICABLE SPECS. :

IMM SPECS



NO-SKIVE hose. A line dedicated to tipper applications. Safety factor 2,5:1.








Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness oil and water resistant.

Reinforcement: 1 braid (DN19) or 2 braids (DN25) made of high tensile steel wire.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glycol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 125°), from -40 to +70°C for water based fluids, from 0 to +70°C water.

													
Part number	ID		Size	OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm		mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TTRK250-12	3/4"	19.0	12	26.0	250	3625	625	9063	180	7.087	0.534	0.359	001C-12
TTRK250-16	1"	25.4	16	35.8	250	3625	625	9063	250	9.843	1.171	0.787	001C-16

MARKING: Mylar version

ih INTERPUMP **HYTRUCK** DN 19 I.D. 3/4" W.P. 250 bar/3625 psi - S.F. 2,5:1