

HOT WATER/6NL


TGLSL 050

ht

HOT WATER/20NL

TGLSL 177

ht



WATER - W.P.20 BAR - PEAKS 120°C - ISO 1307



IMPIEGO

Tubo in gomma long length idoneo per mandata di acqua calda e liquidi antigelo.

- **Temperatura:** -40°C +120°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera EPDM resistente al calore.
- **Rinforzi:** inserzioni di filati sintetici ad alta resistenza.
- **Copertura:** in gomma nera EPDM resistente all'abrasione e agli agenti atmosferici.
- **Superficie:** liscia estrusa.
- **Marcatura:** ad inchiostro "H.T. - HOT WATER - W.P. 20 BAR - PEAKS 120°C - ISO 1307"



APPLICATION

Long length rubber hose suitable for delivery of hot water and anti-freeze liquids.

- **Temperature range:** -40°C +120°C

APPLICATION

Tube: black, smooth heat resistant EPDM rubber.

Reinforcement: high strength synthetic textile yarn.

Cover: black, abrasion and weathering resistant EPDM rubber.

Surface: smooth extruded.

Branding: ink marking "H.T. - HOT WATER - W.P. 20 BAR - PEAKS 120°C - ISO 1307"

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS.ESERCIZIO WORKING PRESSURE		PRESSIONE DI SCOPPIO BRUST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
6NL											
15	19/32"	23	29/32"	0.27	0.18	6	90	18	270	25	82
20NL											
8	5/16"	15	19/32"	0.18	0.12	20	300	60	900	40	131
10	3/8"	17	21/32"	0.21	0.14	20	300	60	900	40	131
13	1/2"	20	3/4"	0.25	0.21	20	300	60	900	40	131
16	5/8"	23	29/32"	0.27	0.22	20	300	60	900	40	131
19	3/4"	27	1.1/16"	0.39	0.26	20	300	60	900	40	131
25	1"	34	1.3/8"	0.58	0.39	20	300	60	900	40	131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Rev. 1