SABBIA/SP6C/PA

TGMSD 113

IMPIEGO

Tubo in gomma spiralato ondulato idoneo per aspirazione e mandata in impieghi gravosi di sabbia, vetro, ceramica o graniglia metallica.

- ***Temperatura:*** -40°C +70°C

STRUTTURA

- ***Sottostrato:*** liscio in para beige resistente all'abrasione.
- ***Rinforzi:*** tessuti sintetici ad alta resistenza, spirale metallica e cordicella di rame.
- ***Copertura:*** in gomma nera NR/SBR resistente all'abrasione e agli agenti atmosferici.
- ***Superficie:*** ondulata.
- ***Marcatura:*** listino arancio scritta nera "H.T. – BULK MATERIAL – S/D"

APPLICATION

Long lasting heavy duty hardwall corrugated cover rubber hose suitable for suction and delivery of sand, glass, ceramics and cast steel shot.

- ***Temperature range:*** -40°C +70°C

CONSTRUCTION

- ***Tube:*** beige, smooth, abrasion resistant para rubber.
- ***Reinforcement:*** high strength synthetic textile plies, helix wire e copper wire.
- ***Cover:*** black, abrasion and weathering resistant antistatic NR/SBR rubber.
- ***Surface:*** corrugated fabric finished.
- ***Branding:*** orange transfer tape black lettering "H.T. – BULK MATERIAL – S/D"

DIAMETRO INTERNO *INSIDE DIAMETER*		PESO TEORICO *WEIGHT*		PRESS. ESERCIZIO *WORKING PRESSURE*		PRESS. SCOPPIO *BURST PRESSURE*		ASPIRAZ. *VACUUM*	RAGGIO CURVATURA *BENDING RADIUS*		LUNGHEZZA *LENGTH*	
mm	inch	mm	inch	bar	psi	bar	psi	bar	mm	inch	mt	ft
51	2"	1,35	0,91	6	90	18	270	0,9	75	2,95	20/40	65.5/131
76	3"	2,00	1.35"	6	90	18	270	0,9	110	4.33"	20/40	65.5/131
102	4"	3,20	2.16"	6	90	18	270	0,9	150	5.90"	20/40	65.5/131
127	5"	4,40	2,95	6	90	18	270	0,9	190	7.48"	20/40	65.5/131
152	6"	5,40	3,62	6	90	18	270	0,9	230	9.06"	20/40	65.5/131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Rev. 0