

## S Clean 50

CK 50



### Technical features

**Number of Nozzles** ..... 10 to suit hose ID  
**Compressed Air** ..... 7 bar  
**Minimum internal diameter of Hose** ..... 6 mm  
**Maximum internal diameter** ..... 51 mm  
**Includes 575 pellets & projectile catcher**

## S Test 2500

BE 2500



### Technical features

**Indicative capacity** ..... 3/16" up to 2"  
**Maximum pressure** ..... 2500 bar  
**Hose connection** ..... 5 outlets ports of 3/8" Fem. Gas (BSPP)  
**Minimum compressed air input** ..... 7 bar with min air flow 1000 l/min (dry air)  
**Standard fluid used for tests** ..... Filtered water, minimum inlet pressure 3 bar  
**Minimum recommended test pressure** ..... 80 bar  
**Dimensions** ..... 2500 x 800 x 1050 mm - 175 kg  
**Packing details** ..... 2360 x 1130 x 1330 mm - 330 kg

## S Mark 50

MMJT-50



### Technical features

**Indicative capacity** ..... 2"  
**Standard stamp holder** ..... 2 x 14 stamps  
**Size of the stamps** ..... 6 x 3 mm  
**Height of the writing** ..... 2,5 mm  
**Max O.D of ferrule** ..... 150 mm  
**Dimensions** ..... 390 x 360 x 520 mm - 34 kg  
**Packing details** ..... 800 x 600 x 830 mm - 50 kg  
**Includes Stamp box of 100 stamps + 20 blanks**

### Options



Computer & printer for test reports

Internal light

Second pump for low pressure

Test with emulsion in filtered closed circuit