



INTERPUMP

BOP FIRESCREEN 5000



**THE INTERPUMP BOP FIRESCREEN 5000 ENSURES
THE HIGHEST SAFETY LEVEL IN HEAVIEST
WORKING CONDITIONS**



I.M.M.
HYDRAULICS



INTERPUMP

BOP FIRESCREEN 5000

INTERPUMP BOP FIRESCREEN 5000

is designed and manufactured to ensure the best reliability in any working conditions.

THE IMM special RED cover enables to match the API16-D requirement without the use of any external steel guard

Six High Tensile Steel Wire Spirals construction for high working pressure and reliability



part number														
	ID			OD	Max WP		Min BP		Min BR		Weight (approx)			
	in	mm			mm	bar	psi	bar	psi	mm	inch	Kg/m	lb/ft	
TBOP350N32	2 "	50,8	32	71,5	350	5075	1400	20300	635	25,000	6,890	4,629	0013-32	

Applicable specification: API-16D – LLOYD'S REGISTER OD 1000/499 rev 2

Recommended fluid:

Hydraulic fluid petroleum based, glycol-water based, lubricant

Operating temperature range:

From -40 to +120°C (petroleum based fluid) 125° intermittent

From -40 to +70°C water based fluids

From 0 to +70°C water

